



Certificate number: 2305724 (1)

Issued 23/05/2023

Expires 23/05/2028

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Brandoni S.p.A.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Brandoni S.p.A.
Via Novara 199
28078
Romagnano Sesia (NO)
Italy



KUKreg4

Product Certificate

Appendix to Certificate number: 2305724

The following products belong to this certificate

<p>PRODUCT DESCRIPTION 'J9' (wafer type) & 'L9' (lug type) ranges of butterfly valves with stainless steel bodies, stainless steel discs and EPDM seats. The products are supplied with either a lever or rotating wheel operating members. AT33 – Without Production Surveillance.</p>
<p>MODEL(S) L9.128 Butterfly valve Lug type DN 40-50-65-80-100-125-150-200-250-300-350-400 with threaded holes for flange bolt connection</p> <p>J9.128 Butterfly valve Wafer type DN 40-50-65-80-100-125-150-200-250-300-350-400 with eyelet hole for trough flange bolt connection</p> <p>J9.628 Butterfly valve Wafer type DN 40-50-65-80-100-125-150-200-250 with eyelet hole for trough flange bolt connection</p>
<p>SIZE: See models.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 16 Bar & maximum operating temperature 85°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C. Above ground use only.</p>
<p>MARKING Brandoni, PN, year of manufacture (YYYY) cast on body.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes